

COLLE PVC GEL PLUS



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : COLLE PVC GEL PLUS
UFI : UMU0-J2TE-2603-DSGY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Adhesive

1.3. Details of the supplier of the safety data sheet

Registered company name : GEB.
Address : CS 62062.95972.ROISSY CDG CEDEX . France.
Telephone : +33 1 48 17 99 99. Fax : +33 1 48 17 98 00.
geb@geb.fr
www.geb.fr

1.4. Emergency telephone number : +33 1 45 42 59 59.

Association/Organisation : INRS.

Other emergency numbers

N/A

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Repeated exposure may cause skin dryness or cracking (EUH066).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Hazard pictograms :



GHS02



GHS07

Signal Word :

DANGER

Product identifiers :

606-001-00-8

ACETONE

Hazard statements :

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing dust/gas/spray.

COLLE PVC GEL PLUS

P280	Wear protective gloves/eye protection/face protection.
Precautionary statements - Response : P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Precautionary statements - Storage : P403 + P235	Store in a well-ventilated place. Keep cool.
Precautionary statements - Disposal : P501	Discard content/container according to applicable regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 59 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

>SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

> Composition :

Identification	Classification (EC) 1272/2008	Note	%
INDEX: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 REACH: 01-2119471330-49 ACETONE	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[i]	50 \leq x % < 100
INDEX: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0 REACH: 01-2119457290-43 BUTANONE	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[i]	10 \leq x % < 25
INDEX: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 REACH: 01-2119475103-46 ETHYL ACETATE	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[i]	10 \leq x % < 25

Information on ingredients :

(Full text of H-phrases: see section 16)

[i] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

COLLE PVC GEL PLUS

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

COLLE PVC GEL PLUS

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

>SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

COLLE PVC GEL PLUS

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

> Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

>SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

> Occupational exposure limits :

- European Union :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
67-64-1	1210	500	-	-	-
78-93-3	600	200	900	300	-
141-78-6	734	200	1468	400	-

- UK :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
67-64-1	500 ppm 1210 mg/m3	1500 ppm 3620 mg/m3			
78-93-3	200 ppm 600 mg/m3	300 ppm 899 mg/m3		Sk. BMGV	
141-78-6	200 ppm 734 mg/m3	400 ppm 1468 mg/m3			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

BUTANONE (CAS: 78-93-3)

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
1161 mg/kg body weight/day

Inhalation.
Long term systemic effects.
600 mg of substance/m3

Consumers.

Ingestion.
Long term systemic effects.
31 mg/kg body weight/day

Dermal contact.
Long term systemic effects.
412 mg/kg body weight/day

Inhalation.
Long term systemic effects.
106 mg of substance/m3

Predicted no effect concentration (PNEC):

BUTANONE (CAS: 78-93-3)

Environmental compartment:

Soil.

COLLE PVC GEL PLUS

PNEC :	22.5 mg/kg
Environmental compartment: PNEC :	Fresh water. 55.8 mg/l
Environmental compartment: PNEC :	Sea water. 55.8 µg/l
Environmental compartment: PNEC :	Intermittent waste water. 55.8 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 284.7 mg/kg
Environmental compartment: PNEC :	Marine sediment. 284.7 µg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 709 mg/l
Environmental compartment: PNEC :	Vermivore predators (oral). 1000 mg/m3

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard ISO 16321.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

Thk : 0.075 mm

> - Body protection

Avoid skin contact.

Wear suitable protective clothing.

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

COLLE PVC GEL PLUS

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

|> - Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

|>SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state : Viscous liquid.

Colour

Unspecified

Odour

Odour threshold : Not stated.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : > 35°C

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) Not stated.

:

Explosive properties, upper explosivity limit (%) Not stated.

:

Flash point

Flash Point : -10.00 °C.

Auto-ignition temperature

Self-ignition temperature : Not relevant.

Decomposition temperature

Decomposition point/decomposition range : Not relevant.

pH

pH (aqueous solution) : Not stated.

pH : Not relevant.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Insoluble.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Not relevant.

Density and/or relative density

Density : < 1

COLLE PVC GEL PLUS

Relative vapour density

Vapour density : Not stated.

> Particle characteristics

The mixture does not contain nanoforms.

> 9.2. Other information

VOC (g/l) : 733.10

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

>SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

> 10.5. Incompatible materials

Keep away from :

- oxidising material

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

>SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

> 11.1.1. Substances

a) Acute toxicity :

No data available.

b) Skin corrosion/skin irritation :

No data available.

c) Serious damage to eyes/eye irritation :

No data available.

d) Respiratory or skin sensitisation :

No data available.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

COLLE PVC GEL PLUS

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

> 11.1.2. Mixture

11.1.2.1 Information on hazard classes

> a) Acute toxicity :

Oral route :

No data available.

No data available.

Dermal route :

b) Skin corrosion/skin irritation :

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

c) Serious damage to eyes/eye irritation :

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

d) Respiratory or skin sensitisation :

No data available.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2.2 Other information

Symptoms related to the physical, chemical and toxicological characteristics

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

11.2. Information on other hazards

> Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

COLLE PVC GEL PLUS

>SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

> 12.6. Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2022 [41-22] - ICAO/IATA 2024 [65]).

14.1. UN number or ID number

1133

14.2. UN proper shipping name

UN1133=ADHESIVES containing flammable liquid

14.3. Transport hazard class(es)

- Classification :



3

14.4. Packing group

II

14.5. Environmental hazards

-

COLLE PVC GEL PLUS

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	5 L	640C	E2	2	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	3	-	II	5 L	F-E, S-D	-	E2	Category B	-

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	II	353	5 L	364	60 L	A3	E2
	3	-	II	Y341	1 L	-	-	A3	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

>SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

> Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2024/2564. (ATP 22)

Container information:

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

Particular provisions :

No data available.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):
<https://echa.europa.eu/substances-restricted-under-reach>.

> Authorisations agreed under Title VII of Regulation (EC) No.1907/2006 (REACH):

The mixture does not contain any substance subject to authorisation according to Annex XIV of REACH Regulation (EC) No 1907/2006: <https://echa.europa.eu/fr/authorisation-list>.

> Substances that deplete the ozone layer (EC Regulation No. 1005/2009, Montreal Protocol) :

The mixture does not contain any substance posing a risk to the ozone layer.

Persistent organic pollutants (POP) (Regulation (EU) 2019/1021):

The mixture does not contain a persistent organic pollutant.

> PIC Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (Rotterdam Convention):

The mixture is not subject to the Prior Informed Consent (PIC) procedure.

Explosives precursors :

The mixture contains at least one substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors:

- Acetone (CAS 67-64-1)

The acquisition, introduction, possession or use of this restricted explosive precursor by members of the general public is subject to the reporting obligations.

15.2. Chemical safety assessment

No data available.

COLLE PVC GEL PLUS

>SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

> Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

> Abbreviations and acronyms :

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

GHS02 : Flame

GHS07 : Exclamation mark

IATA : International Air Transport Association.

IMDG : International Maritime Dangerous Goods.

ICAO : International Civil Aviation Organisation

PBT: Persistent, bioaccumulable and toxic.

PIC: Prior Informed Consent.

POP: Persistent Organic Pollutant.

RID : Regulations concerning the International carriage of Dangerous goods by rail.

SVHC : Substances of very high concern.

vPvB : Very persistent, very bioaccumulable.

WGK : Wassergefährdungsklasse (Water Hazard Class).

> Modification compared to the previous version