# SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°2 (05/03/2025) GEB

# GEBSOPLAST\_SPECIALE\_IRRIGATION



# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

# SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : GEBSOPLAST\_SPECIALE\_IRRIGATION

UFI: UF71-E226-A60D-PVWV

**1.2. Relevant identified uses of the substance or mixture and uses advised against** Adhesive

# 1.3. Details of the supplier of the safety data sheet

Registered company name : GEB.

Address : CS 62062.95972.ROISSY CDG CEDEX . France.

Telephone : +33 1 48 17 99 99. Fax : +33 1 48 17 98 00.

geb@geb.fr

www.geb.fr

## 1.4. Emergency telephone number : +33 1 45 42 59 59.

Association/Organisation : INRS.

## Other emergency numbers

N/A

# SECTION 2 : HAZARDS IDENTIFICATION

# 2.1. Classification of the substance or mixture

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Carcinogenicity, Category 2 (Carc. 2, H351).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

## 2.2. Label elements

Hazard pictograms :





```
GHS08
                 GHS02
                                  GHS07
Signal Word :
DANGER
Product identifiers :
EC 203-726-8
                      TETRAHYDROFURAN
Hazard statements :
H225
                                           Highly flammable liquid and vapour.
H302
                                           Harmful if swallowed.
H319
                                           Causes serious eye irritation.
H335
                                           May cause respiratory irritation.
H336
                                           May cause drowsiness or dizziness.
H351
                                           Suspected of causing cancer.
```

- from hort hot conformed and control of and then in it is

# GEBSOPLAST\_SPECIALE\_IRRIGATION

Precautionary statements - Prevention :
P210

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection/face protection.
Precautionary statements - Response :	
P301 + P312	IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Precautionary statements - Storage :	
P403 + P235	Store in a well-ventilated place. Keep cool.
Precautionary statements - Disposal :	
P501	Discard content/container according to applicable regulations.

## 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 59 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

# SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

# 3.2. Mixtures

a	
Composition	٠
Composition	٠

Identification	Classification (EC) 1272/2008	Note	%
CAS: 109-99-9	GHS07, GHS08, GHS02	[i]	50 <= x % < 100
EC: 203-726-8	Dgr	[ii]	
REACH: 01-2119444314-46	Flam. Liq. 2, H225		
	Acute Tox. 4, H302		
TETRAHYDROFURAN	Eye Irrit. 2, H319		
	STOT SE 3, H335		
	STOT SE 3, H336		
	Carc. 2, H351		
INDEX: 606-002-00-3	GHS02, GHS07	[i]	10 <= x % < 25
CAS: 78-93-3	Dgr		
EC: 201-159-0	Flam. Liq. 2, H225		
REACH: 01-2119457290-43	Eye Irrit. 2, H319		
	STOT SE 3, H336		
BUTANONE	EUH066		
CAS: 1330-20-7	GHS06, GHS08, GHS02	С	0 <= x % < 0.1
EC: 215-535-7	Dgr	[i]	
REACH: 01-2119488216-32	Flam. Liq. 3, H226		
	Asp. Tox. 1, H304		
XYLENE	Acute Tox. 4, H312		
	Skin Irrit. 2, H315		
	Eye Irrit. 2, H319		
	Acute Tox. 3, H331		
	STOT SE 3, H335		
	STOT RE 2, H373		
	Aquatic Chronic 3, H412		

INDEX: 603-108-00-1	GHS02, GHS05, GHS07	[i]	0 <= x % < 0.1
CAS: 78-83-1	Dgr		
EC: 201-148-0	Flam. Liq. 3, H226		
	STOT SE 3, H335		
2-METHYLPROPAN-1-OL	Skin Irrit. 2, H315		
	Eye Dam. 1, H318		
	STOT SE 3, H336		
INDEX: 601-023-00-4	GHS02, GHS07, GHS08	[i]	0 <= x % < 0.1
CAS: 100-41-4	Dgr		
EC: 202-849-4	Flam. Liq. 2, H225		
REACH: 01-2119489370-35	Acute Tox. 4, H332		
	STOT RE 2, H373		
ETHYLBENZENE	Asp. Tox. 1, H304		

#### Specific concentration limits:

specific concentration millis.		
Identification	Specific concentration limits	ATE
CAS: 109-99-9	Eye Irrit. 2: H319 C>= 25%	inhalation: $ATE = 14.7 \text{ mg/l}$
EC: 203-726-8		(dust/mist)
REACH: 01-2119444314-46		
TETRAHYDROFURAN		
CAS: 1330-20-7		inhalation: $ATE = 5.53 \text{ mg/l}$
EC: 215-535-7		(dust/mist)
REACH: 01-2119488216-32		dermal: ATE = $1001 \text{ mg/kg BW}$
VVI ENE		

# XYLENE

# Information on ingredients :

(Full text of H-phrases: see section 16)

[i] Substance for which maximum workplace exposure limits are available.

[ii] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

## **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

## 4.1. description of first aid measures

#### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

## In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

#### In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

# 4.2. Most important symptoms and effects, both acute and delayed

No data available.

# 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

# **SECTION 5 : FIREFIGHTING MEASURES**

## Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

#### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

# Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

## 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

## **5.3.** Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

# SECTION 6 : ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### **6.2.** Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

# 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

# 6.4. Reference to other sections

No data available.

## **SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

## 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

#### Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

# **Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

## 7.2. Conditions for safe storage, including any incompatibilities

#### No data available.

## Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

# Packaging

Always keep in packaging made of an identical material to the original.

#### 7.3. Specific end use(s)

No data available.

# SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

#### **Occupational exposure limits :**

#### - European Union :

CAS	VME-mg/m3	: VME-ppm :	VLE-mg/m3:	VLE-ppm :	Notes :
109-99-9	150	50	300	100	Peau
78-93-3	600	200	900	300	-
1330-20-7	221	50	442	100	Peau
100-41-4	442	100	884	200	Peau
- UK :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
109-99-9	50 ppm	100 ppm		Sk	
	150 mg/m3	300 mg/m3			
78-93-3	200 ppm	300 ppm		Sk. BMGV	
	600 mg/m3	899 mg/m3			
1330-20-7	50 ppm	100 ppm		Sk. BMGV	
	220 mg/m3	441 mg/m3			
78-83-1	50 ppm	75 ppm			
	154 mg/m3	231 mg/m3			
100-41-4	100 ppm	125 ppm		Sk	
	441 mg/m3	552 mg/m3			

# Derived no effect level (DNEL) or derived minimum effect level (DMEL):

BUTANONE (CAS: 78-93-3) Final use:

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

#### Final use:

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

TETRAHYDROFURAN (CAS: 109-99-9) **Final use:** Exposure method:

Potential health effects: DNEL :

Exposure method:

Workers. Dermal contact. Long term systemic effects. 1161 mg/kg body weight/day

Inhalation. Long term systemic effects. 600 mg of substance/m3

**Consumers.** Ingestion. Long term systemic effects. 31 mg/kg body weight/day

Dermal contact. Long term systemic effects. 412 mg/kg body weight/day

Inhalation. Long term systemic effects. 106 mg of substance/m3

#### Workers.

Dermal contact. Long term systemic effects. 25 mg/kg body weight/day

Inhalation.

# SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°2 (05/03/2025) GEB

# GEBSOPLAST\_SPECIALE\_IRRIGATION

Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

## Predicted no effect concentration (PNEC):

BUTANONE (CAS: 78-93-3) Environmental compartment: PNEC :

TETRAHYDROFURAN (CAS: 109-99-9) Environmental compartment: PNEC :

Environmental compartment: PNEC :

Environmental compartment: PNEC :

Environmental compartment: PNEC :

Environmental compartment:

Long term local effects. 150 mg of substance/m3

Inhalation. Long term systemic effects. 150 mg of substance/m3

Inhalation. Short term local effects. 300 mg of substance/m3

Inhalation. Short term systemic effects. 300 mg of substance/m3

Soil. 22.5 mg/kg

Fresh water. 55.8 mg/l

Sea water. 55.8 µg/l

Intermittent waste water. 55.8 mg/l

Fresh water sediment. 284.7 mg/kg

Marine sediment. 284.7 µg/kg

Waste water treatment plant. 709 mg/l

Vermivore predators (oral). 1000 mg/m3

Soil. 2.13 mg/kg

Fresh water. 4.32 mg/l

Sea water. 0.432 mg/l

Intermittent waste water. 21.6 mg/l

Waste water treatment plant.

PNEC :

4.6 mg/l

#### 8.2. Exposure controls

#### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

# - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard ISO 16321.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

Thk : 0.075 mm

## - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

## - Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

# SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Physical state Physical state :	Viscous liquid.
Colour Unspecified	
<b>Odour</b> Odour threshold :	Not stated.
Melting point Melting point/melting range :	Not relevant.
<b>Freezing point</b> Freezing point / Freezing range :	Not stated.
<b>Boiling point or initial boiling point and boiling</b> Boiling point/boiling range :	s range > 35°C

<b>Flammability</b> Flammability (solid, gas) :	Not stated.	
<b>Lower and upper explosion limit</b> Explosive properties, lower explosivity limit (%)Not stated.		
: Explosive properties, upper explosivity limit (% :	)Not stated.	
<b>Flash point</b> Flash Point :	-4.00 °C.	
Auto-ignition temperature Self-ignition temperature :	Not relevant.	
<b>Decomposition temperature</b> Decomposition point/decomposition range :	Not relevant.	
<b>pH</b> pH (aqueous solution) : pH :	Not stated. Not relevant.	
<b>Kinematic viscosity</b> Viscosity :	Not stated.	
<b>Solubility</b> Water solubility : Fat solubility :	Insoluble. Not stated.	
Partition coefficient n-octanol/water (log value) Partition coefficient: n-octanol/water :	) Not stated.	
<b>Vapour pressure</b> Vapour pressure (50°C) :	Not relevant.	
<b>Density and/or relative density</b> Density :	0.92-0.94	
<b>Relative vapour density</b> Vapour density :	Not stated.	
<b>Particle characteristics</b> The mixture does not contain nanoforms.		
<b>9.2. Other information</b> VOC (g/l) :	775.32	
<b>9.2.1. Information with regard to physical hazard classes</b> No data available.		
<b>9.2.2. Other safety characteristics</b> No data available.		

# SECTION 10 : STABILITY AND REACTIVITY

# 10.1. Reactivity

No data available.

## **10.2.** Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### **10.3.** Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

## 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.

-	heating

- heat

# - flames and hot surfaces

# 10.5. Incompatible materials

No data available.

# 10.6. Hazardous decomposition products

- The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO2)

# SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in	<b>Regulation (EC) No 1272/2008</b>
11.1.1. Substances	
a) Acute toxicity :	
XYLENE (CAS: 1330-20-7) Dermal route :	LD50 = 1001 mg/kg body weight
Definal foute.	LD30 = 1001 mg/kg body weight
Inhalation route (Dusts/mist) :	LC50 = 5.53 mg/l
TETRAHYDROFURAN (CAS: 109-99-9)	
Oral route :	LD50 > 1650 mg/kg body weight Species : Rat
Dermal route :	LD50 >= 2000 mg/kg body weight Species : Rat
Inhalation route (Dusts/mist) :	LC50 = 14.7 mg/l
b) Skin corrosion/skin irritation :	
No data available.	
c) Serious damage to eyes/eye irritation :	
No data available.	
d) Respiratory or skin sensitisation :	
No data available.	
e) Germ cell mutagenicity : No data available.	
f) Carcinogenicity :	
No data available.	
g) Reproductive toxicant :	
No data available.	
h) Specific target organ systemic toxicity - single	exposure :
No data available.	
i) Specific target organ systemic toxicity - repeated No data available.	ed exposure :
j) Aspiration hazard :	
No data available.	
11.1.2. Mixture	
11.1.2.1 Information on hazard classes	
a) Acute toxicity :	
Oral route :	Harmful if swallowed.

No data available.

#### Dermal route :

## b) Skin corrosion/skin irritation :

No data available.

# c) Serious damage to eyes/eye irritation :

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage

#### d) Respiratory or skin sensitisation :

No data available.

# e) Germ cell mutagenicity :

No data available.

## f) Carcinogenicity :

Suspected human carcinogen.

## g) Reproductive toxicant :

No data available.

#### h) Specific target organ systemic toxicity - single exposure :

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties. Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

#### i) Specific target organ systemic toxicity - repeated exposure :

No data available.

## j) Aspiration hazard :

No data available.

#### 11.1.2.2 Other information

#### Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 100-41-4 : IARC Group 2B : The agent is possibly carcinogenic to humans.

CAS 1330-20-7 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 109-99-9 : IARC Group 2B : The agent is possibly carcinogenic to humans.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

# SECTION 12 : ECOLOGICAL INFORMATION

# 12.1. Toxicity

# 12.1.1. Substances

XYLENE (CAS: 1330-20-7) Fish toxicity :

Crustacean toxicity :

LC50 = 2.6 mg/l Duration of exposure : 96 h

EC50 = 1 mg/l Duration of exposure : 48 h

Algae toxicity :

ECr50 = 2.2 mg/l Duration of exposure : 72 h

TETRAHYDROFURAN (CAS: 109-99-9) Fish toxicity :

LC50 = 2160 mg/l Duration of exposure : 96 h

Crustacean toxicity :	EC50 = 5930 mg/l Duration of exposure : 24 h
12.1.2. Mixtures	
No aquatic toxicity data available for the mixture.	
12.2. Persistence and degradability	
12.2.1. Substances	
XYLENE (CAS: 1330-20-7) Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
TETRAHYDROFURAN (CAS: 109-99-9) Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
12.3. Bioaccumulative potential	
12.3.1. Substances	
TETRAHYDROFURAN (CAS: 109-99-9) Octanol/water partition coefficient :	$\log \text{Koe} = 0.46$
12.4. Mobility in soil	
No data available.	
12.5. Results of PBT and vPvB assessment	
No data available.	
12.6. Endocrine disrupting properties	
-	tted as an endocrine disruptor with environmental effects.
12.7. Other adverse effects	
No data available.	
SECTION 13 : DISPOSAL CONSIDERATIONS	
Proper waste management of the mixture and/or its	s container must be determined in accordance with Directive 2008/98/EC.
13.1. Waste treatment methods	
Do not pour into drains or waterways.	
Waste :	
without risk to water, air, soil, plants or animals.	gering human health, without harming the environment and, in particular
	rrent legislation, via a certified collector or company.
Do not contaminate the ground or water with waste	e, do not dispose of waste into the environment.
Soiled packaging :	
Empty container completely. Keep label(s) on cont	ainer.
Give to a certified disposal contractor.	
SECTION 14 : TRANSPORT INFORMATION	
Transport product in compliance with provisions transport (ADR 2023 - IMDG 2022 [41-22] - ICA	of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air O/IATA 2024 [65]).
14.1. UN number or ID number	
1133	

# 14.2. UN proper shipping name

\_

UN1133=ADHESIVES containing flammable liquid

- Made under licence of European Label System® MSDS software from InfoDyne - http://www.infodyne.fr -

#### 14.3. Transport hazard class(es)



14.4. Packing group

Π

14.5. Environmental hazards

\_

## 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	5 L	640D	E2	2	D/E
	-			_						_
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage	Segregation	
								Handling		
	3	-	II	5 L	F-E. S-D	-	E2	Category B	-	
	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	3	-	II	353	5 L	364	60 L	A3	E2	
	3	-	П	Y341	1 L	-	-	A3	E2	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

# 14.7. Maritime transport in bulk according to IMO instruments

No data available.

# **SECTION 15 : REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2024/2564. (ATP 22)

#### **Container information:**

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

#### **Particular provisions :**

No data available.

# Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

#### Authorisations agreed under Title VII of Regulation (EC) No.1907/2006 (REACH):

The mixture does not contain any substance subject to authorisation according to Annex XIV of REACH Regulation (EC) No 1907/2006: https://echa.europa.eu/fr/authorisation-list.

# Substances that deplete the ozone layer (EC Regulation No. 1005/2009, Montreal Protocol) :

The mixture does not contain any substance posing a risk to the ozone layer.

#### Persistent organic pollutants (POP) (Regulation (EU) 2019/1021):

The mixture does not contain a persistent organic pollutant.

#### PIC Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (Rotterdam Convention):

The mixture is not subject to the Prior Informed Consent (PIC) procedure.

#### **Explosives precursors :**

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

#### 15.2. Chemical safety assessment

No data available.

# **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

#### Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure .
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50: The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

GHS02 : Flame

GHS07 : Exclamation mark

GHS08 : Health hazard

IATA : International Air Transport Association.

 $\label{eq:IMDG} \textbf{IMDG}: \textbf{International Maritime Dangerous Goods}.$ 

ICAO : International Civil Aviation Organisation

PBT: Persistent, bioaccumulable and toxic.

PIC: Prior Informed Consent.

POP: Persistent Organic Pollutant.

RID : Regulations concerning the International carriage of Dangerous goods by rail.

SVHC : Substances of very high concern.

vPvB : Very persistent, very bioaccumulable.

WGK : Wassergefahrdungsklasse (Water Hazard Class).