

**LUBRIFIANT SILICONE AEROSOL 210ML**



**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

**>SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**> 1.1. Product identifier**

Product name : LUBRIFIANT SILICONE AEROSOL 210ML  
UFI : SUUD-TCD7-R200-E8A5

**> 1.2. Relevant identified uses of the substance or mixture and uses advised against**

N/A

**1.3. Details of the supplier of the safety data sheet**

Registered company name : GEB.  
Address : CS 62062.95972.ROISSY CDG CEDEX . France.  
Telephone : +33 1 48 17 99 99. Fax : +33 1 48 17 98 00.  
geb@geb.fr  
www.geb.fr

**1.4. Emergency telephone number : +33 1 45 42 59 59.**

Association/Organisation : INRS.

**>SECTION 2 : HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**> In compliance with EC regulation No. 1272/2008 and its amendments.**

Aerosol, Category 1 (Aerosol 1, H222 - H229).

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

The propellant gas is taken into account when determining the health and environmental classification of the mixture.

**2.2. Label elements**

Mixture for aerosol application.

**> In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS02

Signal Word :

DANGER

Hazard statements :

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Do not pierce or burn, even after use.

**LUBRIFIANT SILICONE AEROSOL 210ML**

Precautionary statements - Storage :

P410 + P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**> 2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq 0.1\%$  with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

**>SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**> Composition :**

Identification	Classification (EC) 1272/2008	Note	%
INDEX: 601_004_01_8 CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32  BUTANE (CONTAINING $\geq 0,1\%$ % BUTADIENE (203-450-8))	GHS02 Dgr Flam. Gas 1A, H220 Press. Gas, H280	C [1] [7]	25 $\leq x\%$ < 50
INDEX: 246538_78_3 CAS: 246538-78-3 EC: 920-901-0 REACH: 01-2119456810-40  HYDROCARBONS, C11-C13, ISOALKANES, <2% AROMATICS	GHS08 Dgr Asp. Tox. 1, H304 EUH:066		10 $\leq x\%$ < 25
INDEX: 209 CAS: 74-98-6 REACH: 01-2119486557-22  PROPANE	GHS02 Dgr Flam. Gas 1A, H220 Press. Gas, H280	[1] [7]	10 $\leq x\%$ < 25

**Information on ingredients :**

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

[7] Propellant gas

**>SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. description of first aid measures**

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

**In the event of swallowing :**

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**LUBRIFIANT SILICONE AEROSOL 210ML**

---

---

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

---

**|>SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**|> For non first aid worker**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

---

**|>SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**|> 7.1. Precautions for safe handling**

Always wash hands after handling.

Ensure that there is adequate ventilation, especially in confined areas.

**LUBRIFIANT SILICONE AEROSOL 210ML**

**Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

**> Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**>SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**> Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	1000 ppm				
74-98-6	1000 ppm				

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME :	VME :	Excess	Notes
106-97-8		1000 ppm 2400 mg/m3		4(II)
74-98-6		1000 ppm 1800 mg/m3		4(II)

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-

**LUBRIFIANT SILICONE AEROSOL 210ML**

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm 1450 mg/m3	750 ppm 1810 mg/m3		Carc	

**8.2. Exposure controls**

**Personal protection measures, such as personal protective equipment**

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

**> - Hand protection**

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

**> [www.geb.fr](http://www.geb.fr) +33 1**

**48 17 99 99. Fax : +33 1 48 17 98 00.**

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**>SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**Physical state**

Physical state : Fluid liquid.  
Spray.

**> Colour**

Unspecified

**> Odour**

Odour threshold : Not stated.

**> Melting point**

Melting point/melting range : Not relevant.

**> Freezing point**

Freezing point / Freezing range : Not stated.

**> Boiling point or initial boiling point and boiling range**

Boiling point/boiling range : Not relevant.

**> Flammability**

Flammability (solid, gas) : Not stated.

**> Lower and upper explosion limit**

Explosive properties, lower explosivity limit (%) Not stated.

:

Explosive properties, upper explosivity limit (%) Not stated.

:

**> Flash point**

Flash point interval : Not relevant.

**> Auto-ignition temperature**

Self-ignition temperature : Not relevant.

**> Decomposition temperature**

Decomposition point/decomposition range : Not relevant.

**LUBRIFIANT SILICONE AEROSOL 210ML**

---

**|> pH**

pH (aqueous solution) : Not stated.  
pH : Not relevant.

**|> Kinematic viscosity**

Viscosity : Not stated.

**|> Solubility**

Water solubility : Insoluble.  
Fat solubility : Not stated.

**|> Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water : Not stated.

**|> Vapour pressure**

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

**|> Density and/or relative density**

Density : < 1

**|> Relative vapour density**

Vapour density : Not stated.

**|> Particle characteristics**

The mixture does not contain nanoforms.

**9.2. Other information**

No data available.

**9.2.1. Information with regard to physical hazard classes**

No data available.

**|> Aerosols**

Chemical combustion heat :  $\geq 30$  kJ/g.

**9.2.2. Other safety characteristics**

No data available.

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

**10.5. Incompatible materials**

No data available.

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**LUBRIFIANT SILICONE AEROSOL 210ML**

---

---

**>SECTION 11 : TOXICOLOGICAL INFORMATION**

**> 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Splashes in the eyes may cause irritation and reversible damage

**11.1.1. Substances**

No toxicological data available for the substances.

**11.1.2. Mixture**

No toxicological data available for the mixture.

**11.2. Information on other hazards**

---

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

No data available.

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

---

**>SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2022 [41-22] - ICAO/IATA 2023 [64]).

**14.1. UN number or ID number**

1950

**14.2. UN proper shipping name**

UN1950=AEROSOLS, flammable

**LUBRIFIANT SILICONE AEROSOL 210ML**

**14.3. Transport hazard class(es)**

- Classification :



2.1

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D

>	IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
		2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A802	E0
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Maritime transport in bulk according to IMO instruments**

No data available.

**>SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**> Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

**Container information:**

No data available.

**> Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):**

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):  
<https://echa.europa.eu/substances-restricted-under-reach>.

**> Explosives precursors :**

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

**Particular provisions :**

No data available.

**15.2. Chemical safety assessment**

No data available.



**LUBRIFIANT SILICONE AEROSOL 210ML**

---

**>SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
EUH066	Repeated exposure may cause skin dryness or cracking.

**> Abbreviations and acronyms :**

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.

> Modification compared to the previous version