

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673



>

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE
Product code : 114673.
UFI : ND2K-P6HC-T30R-913H

1.2. Relevant identified uses of the substance or mixture and uses advised against

anaerobic resin
Read the technical data sheet for the operating procedure and an effective result

1.3. Details of the supplier of the safety data sheet

Registered company name : GEB.
Address : CS 62062.95972.ROISSY CDG CEDEX . France.
Telephone : 01 48 17 99 99. Fax : 01 48 17 98 00.
geb@geb.fr
www.geb.fr

1.4. Emergency telephone number : 01 45 42 59 59.

Association/Organisation : INRS.

>SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).
Eye irritation, Category 2 (Eye Irrit. 2, H319).
Skin sensitisation, Category 1 (Skin Sens. 1, H317).
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).
Hazardous to the aquatic environment - Chronic hazard, Category 4 (Aquatic Chronic 4, H413).
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07

Signal Word :

WARNING

Product identifiers :

607-124-00-X	2-HYDROXYETHYL METHACRYLATE
EC 201-177-9	ACRYLIC ACID
EC 203-742-5	MALEIC ACID

Hazard statements :

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

H413	May cause long lasting harmful effects to aquatic life.
Precautionary statements - General :	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary statements - Prevention :	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P302 + P352	IF ON SKIN: Wash with plenty of water/...
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or a doctor if you feel unwell.
Precautionary statements - Disposal :	
P501	Discard content/container according to applicable regulations.

> 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances >= 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

>SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

> Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 130614 CAS: 41637-38-1 EC: 609-946-4 REACH: 01-2119980659-17 BISPHENOL A ETHOXYLATE DIMETHACRYLATE	Aquatic Chronic 4, H413		50 <= x % < 100
INDEX: 607-124-00-X CAS: 868-77-9 EC: 212-782-2 REACH: 01-2119490169-29 2-HYDROXYETHYL METHACRYLATE	GHS07 Wng Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317		25 <= x % < 50
INDEX: 607_061_00_8 CAS: 79-10-7 EC: 201-177-9 REACH: 01-2119452449-31 ACRYLIC ACID	GHS07, GHS05, GHS09, GHS02 Dgr Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Acute 1, H400 M Acute = 1	D [1]	2.5 <= x % < 10

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

INDEX: 607_095_00_3 CAS: 110-16-7 EC: 203-742-5 REACH: 01-2119488705-25-XXX MALEIC ACID	GHS07, GHS05 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 STOT SE 3, H335		0 <= x % < 2.5
INDEX: 617_002_00_8 CAS: 80-15-9 EC: 201-254-7 REACH: 01-2119475796-19 ALPHA ,ALPHA-DIMETHYLBENZYL	GHS06, GHS05, GHS09, GHS08, GHS02 Dgr Org. Perox. E, H242 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Acute Tox. 3, H331 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 2, H411		0 <= x % < 2.5
INDEX: 603-027-00-1 CAS: 107-21-1 EC: 203-473-3 REACH: 01-2119456816-28 ETHANEDIOL	GHS07 Wng Acute Tox. 4, H302	[1]	0 <= x % < 2.5

> Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: 130614 CAS: 41637-38-1 EC: 609-946-4 REACH: 01-2119980659-17 BISPHENOL A ETHOXYLATE DIMETHACRYLATE		dermal: ATE = 2000.1 mg/kg BW oral: ATE = 20000.1 mg/kg BW
INDEX: 607_061_00_8 CAS: 79-10-7 EC: 201-177-9 REACH: 01-2119452449-31 ACRYLIC ACID		inhalation: ATE = 3.6 mg/1 4h (dust/mist) dermal: ATE = 2000 mg/kg BW oral: ATE = 1405 mg/kg BW
INDEX: 607_095_00_3 CAS: 110-16-7 EC: 203-742-5 REACH: 01-2119488705-25-XXX MALEIC ACID	Skin Sens. 1: H317 C>= 0.1%	dermal: ATE = 1560 mg/kg BW oral: ATE = 708 mg/kg BW
INDEX: 617_002_00_8 CAS: 80-15-9 EC: 201-254-7 REACH: 01-2119475796-19 ALPHA ,ALPHA-DIMETHYLBENZYL	Skin Corr. 1B: H314 C>= 10% Skin Irrit. 2: H315 3% <= C < 10%	inhalation: ATE = 1.37 mg/1 4h (dust/mist) dermal: ATE = 1.2 mg/kg BW oral: ATE = 382 mg/kg BW

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

>SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

|> 5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

|>SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
79-10-7	29	10	59 (1 min)	20 (1 min)	-
107-21-1	52	20	104	40	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
79-10-7	2 ppm			Skin; A4	
107-21-1	-	-	100	-	-

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME :	VME :	Excess	Notes
79-10-7		10 ppm 30 mg/m ³		1(I)
107-21-1		10 ppm 26 mg/m ³		2(I)

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
79-10-7	10	29	20	59	(14)	-
107-21-1	20	52	40	104	*	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-21-1	20 ppm 52 mg/m ³	40 ppm 104 mg/m ³		Sk	

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

ALPHA ,ALPHA-DIMETHYLBENZYL (CAS: 80-15-9)

Final use:

Exposure method:

Potential health effects:

DNEL :

Workers.

Inhalation.

Long term systemic effects.

6 mg of substance/m3

MALEIC ACID (CAS: 110-16-7)

Final use:

Exposure method:

Potential health effects:

DNEL :

Workers.

Inhalation.

Short term local effects.

3 mg of substance/m3

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Long term systemic effects.

3 mg of substance/m3

Exposure method:

Potential health effects:

Inhalation.

Long term local effects.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

DNEL : 3 mg of substance/m3
Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 3 mg of substance/m3

ACRYLIC ACID (CAS: 79-10-7)

Final use:
Exposure method: **Workers.**
Potential health effects: Dermal contact.
DNEL : Short term local effects.
1 mg of substance/cm2
Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 30 mg of substance/m3

2-HYDROXYETHYL METHACRYLATE (CAS: 868-77-9)

Final use:
Exposure method: **Workers.**
Potential health effects: Dermal contact.
DNEL : Long term systemic effects.
1.3 mg/kg body weight/day
Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 4.9 mg of substance/m3

BISPHENOL A ETHOXYLATE DIMETHACRYLATE (CAS: 41637-38-1)

Final use:
Exposure method: **Workers.**
Potential health effects: Dermal contact.
DNEL : Long term systemic effects.
2 mg/kg body weight/day
Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 3.52 mg of substance/m3

Predicted no effect concentration (PNEC):

ALPHA ,ALPHA-DIMETHYLBENZYL (CAS: 80-15-9)

Environmental compartment: Soil.
PNEC : 1.2 mg/kg
Environmental compartment: Fresh water.
PNEC : 0.0031 mg/l
Environmental compartment: Sea water.
PNEC : 0.00031 mg/l
Environmental compartment: Intermittent waste water.
PNEC : 0.031
Environmental compartment: Fresh water sediment.
PNEC : 0.023 mg/kg
Environmental compartment: Marine sediment.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

PNEC :	0.0023 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 0.35 mg/l
MALEIC ACID (CAS: 110-16-7)	
Environmental compartment: PNEC :	Soil. 0.0415
Environmental compartment: PNEC :	Fresh water. 0.1 mg/l
Environmental compartment: PNEC :	Sea water. 0.01 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.4281 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.334 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.0334 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 44.6 mg/l
ACRYLIC ACID (CAS: 79-10-7)	
Environmental compartment: PNEC :	Fresh water. 0.003 mg/l
Environmental compartment: PNEC :	Sea water. 0 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.001 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.024 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.002 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 0.9 mg/l
2-HYDROXYETHYL METHACRYLATE (CAS: 868-77-9)	
Environmental compartment: PNEC :	Soil. 0.476 mg/kg
Environmental compartment: PNEC :	Fresh water. 3.79 mg/kg
Environmental compartment:	Waste water treatment plant.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

PNEC : 10 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

> - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

> - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

>SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state : Viscous liquid.

> Colour

Unspecified

> Odour

Odour threshold : Not stated.

> Melting point

Melting point/melting range : Not relevant.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

> Freezing point

Freezing point / Freezing range : Not stated.

> Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not relevant.

> Flammability

Flammability (solid, gas) : Not stated.

> Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

Flash point

Flash Point Interval : FP > 100°C.

Auto-ignition temperature

Self-ignition temperature : Not relevant.

Decomposition temperature

Decomposition point/decomposition range : Not relevant.

> pH

pH (aqueous solution) : Not stated.

pH : Not relevant.

> Kinematic viscosity

Viscosity : Not stated.

> Solubility

Water solubility : Insoluble.

Fat solubility : Not stated.

> Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Not relevant.

Density and/or relative density

Density : > 1

> Relative vapour density

Vapour density : Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity :

ALPHA ,ALPHA-DIMETHYLBENZYL (CAS: 80-15-9)

Oral route : LD50 = 382
Species : Rat

Dermal route : LD50 = 1.200 mg/kg

Inhalation route (Dusts/mist) : LC50 = 1.370 mg/l
Duration of exposure : 4 h

MALEIC ACID (CAS: 110-16-7)

Oral route : LD50 = 708 mg/kg
Species : Rat

Dermal route : LD50 = 1560 mg/kg
Species : Rabbit

Inhalation route (Dusts/mist) : LC50 > 720 mg/m³
Species : Rat

ACRYLIC ACID (CAS: 79-10-7)

Oral route : LD50 = 1405 mg/kg
Species : Rat

Dermal route : LD50 = 2000 mg/kg
Species : Rabbit

Inhalation route (Dusts/mist) : LC50 = 3.6 mg/l
Species : Rat
Duration of exposure : 4 h

BISPHENOL A ETHOXYLATE DIMETHACRYLATE (CAS: 41637-38-1)

Oral route : LD50 = 20000.1 mg/kg
Species : Rat

Dermal route : LD50 = 2000.1 mg/kg

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

Skin corrosion/skin irritation :

ALPHA ,ALPHA-DIMETHYLBENZYL (CAS: 80-15-9)

Species : Rabbit

Species : Rabbit

MALEIC ACID (CAS: 110-16-7)

Corrosivity :

Causes severe skin burns.

ACRYLIC ACID (CAS: 79-10-7)

Corrosivity :

Causes severe skin burns.

Effect observed : Erythema score

BISPHENOL A ETHOXYLATE DIMETHACRYLATE (CAS: 41637-38-1)

Other guideline

Other guideline

Serious damage to eyes/eye irritation :

MALEIC ACID (CAS: 110-16-7)

The substance produces at least in one animal effects on the cornea that are not expected to reverse or have not fully reversed within an observation period of normally 21 days.

Reproductive toxicant :

BISPHENOL A ETHOXYLATE DIMETHACRYLATE (CAS: 41637-38-1)

No toxic effect for reproduction

Specific target organ systemic toxicity - single exposure :

ACRYLIC ACID (CAS: 79-10-7)

Dermal route :

C = 440 mg/kg bodyweight

Inhalation route :

C = 1.85 mg/l/4h

11.1.2. Mixture

Acute toxicity :

Inhalation route (Dusts/mist) :

No effect.

Duration of exposure : 4 h

LC50 = 100 mg/l

Skin corrosion/skin irritation :

The irritant classification based on a high/low pH has been confirmed by irritation tests.

Serious damage to eyes/eye irritation :

Causes serious eye irritation.

Corneal haze :

2 ≤ Average score < 3 and effects totally reversible within 21 days of observation

11.2. Information on other hazards

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 79-10-7 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

SECTION 12 : ECOLOGICAL INFORMATION

May cause long lasting harmful effects to aquatic life.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

MALEIC ACID (CAS: 110-16-7)

Fish toxicity :

LC50 = 5 mg/l

Species : Pimephales promelas

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 400 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

Aquatic plant toxicity :

ECr50 = 41 mg/l

Species : Others

Duration of exposure : 72 h

BISPHENOL A ETHOXYLATE DIMETHACRYLATE (CAS: 41637-38-1)

Fish toxicity :

LC50 > 100 mg/l

Species : Oncorhynchus mykiss

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 100 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

ALPHA ,ALPHA-DIMETHYLBENZYL (CAS: 80-15-9)

Fish toxicity :

LC50 = 3.9 mg/l

Species : Oncorhynchus mykiss

Duration of exposure : 96 h

ACRYLIC ACID (CAS: 79-10-7)

Fish toxicity :

LC50 = 22 mg/l

Species : Brachydanio rerio

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 270 mg/l

Species : Daphnia magna

Duration of exposure : 24 h

NOEC = 24.1 mg/l

Species : Daphnia magna

Duration of exposure : 21 days

Algae toxicity :

Aquatic plant toxicity :

ECr50 = 0.04 mg/l

Species : Others

Duration of exposure : 72 h

EC50 mg/l

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

Species : Others
Duration of exposure : 96 h

NOEC = 400 mg/l
Species : Others
Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

ALPHA ,ALPHA-DIMETHYLBENZYL (CAS: 80-15-9)

Biodegradability : Rapidly degradable.

MALEIC ACID (CAS: 110-16-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

ACRYLIC ACID (CAS: 79-10-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

BISPHENOL A ETHOXYLATE DIMETHACRYLATE (CAS: 41637-38-1)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number or ID number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Maritime transport in bulk according to IMO instruments

-

>SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

> - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

> - Container information:

The mixture is contained in packaging that does not exceed 125 ml.

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):
<https://echa.europa.eu/substances-restricted-under-reach>.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

>SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

RESINE ETANCHEITE TOUS FLUIDES EAU POTABLE - 114673

H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

> Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.
LC50 : The concentration of a test substance resulting in 50% lethality in a given period.
EC50 : The effective concentration of substance that causes 50% of the maximum response.
ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.
NOEC : The concentration with no observed effect.
REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.
ATE : Acute Toxicity Estimate
BW : Body Weight
DNEL : Derived No-Effect Level
PNEC : Predicted No-Effect Concentration
UFI : Unique formulation identifier.
STEL : Short-term exposure limit
TWA : Time Weighted Averages
TMP : French Occupational Illness table
TLV : Threshold Limit Value (exposure)
AEV : Average Exposure Value.
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
WGK : Wassergefährdungsklasse (Water Hazard Class).
GHS07 : Exclamation mark
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.
> Modification compared to the previous version