

DILUJOINT

Functionality

Gel effectively removes residues of cross-linked silicone sealants used for sanitary joints (bath, washbasin, sink, WC seals, etc.).

- Easily removes old seals (once initial stripping has been done with the cutter).
- Removes traces of silicone (acetic, alkoxy) from enamelled surface, plastics, glass, stainless steel, aluminium, marble, etc.
- Can be used for all types of seals apart polyurethane, acrylic and MS polymer.

Technical characteristics

Characteristics	Specifications
Appearance	Thixotropic gel
Colour	Colorless transparent
Odour	Slight hydrocarbon smell
Density	0.91
pH	< 2

Use

Preparation

- The surfaces to be treated must be dry.
- It is recommended that as much sealant as possible be removed mechanically first with the cutter.

Instructions for use

- The tube is fitted with a BSE (child-resistant cap) : press and turn simultaneously to open. Turn the cap over to pierce the seal.
- Apply the gel so that the rest of the old joint is completely covered with the product.
- Leave for 30 minutes minimum. Depending on the thickness of the seal residue, you can leave the product to work for up to 12 hours or repeat the operation.
- Remove any residues and softened joint remnants with a dry cloth or scraper.
- Once the surface has been stripped, clean with soapy water, rinse with water and dry. The new sealant can then be applied.

If there is any residue of improperly cleaned product, there is a risk that it will attack the new silicone seal.

Consumption

A 125 mL tube allows to remove about 4.9 m of seal, either the standard size of a bathtub (180 cm x 80 cm, or 3 sides) and a shower tray (70 cm x 70 cm, 2 sides).

Material cleaning

Soapy water

Safety precautions

The Material Safety Data Sheet is available on the Internet on www.quickfds.com or on www.geb.fr .

If the product is subject to detergent regulation : Component list available on request at reach@geb.fr

If the product is subject to biocide regulation or if it contains a biocide to protect it : Consult the Material Safety Data Sheet - Please use the products responsibly.

Comments

Warning : we recommend not leaving the product to at for more than one night at the risk of damaging the supports.

It is preferable to carry out a test beforehand on substates such as raw wood, painted and/or varnished substrates, porous stones and steel : the product may leave irreversible marks on these substrates.

Storage

Store at a temperature between +5°C and +30°C.

The expiry date on packaging is for unopened product stored at 20°C in normal hygrometry conditions.

Packaging and waste sorting

Refer to the information on the product and to the applicable local regulations.

The information contained on the technical datasheet is provided in all good faith and results from measurements made in our laboratory. Given the number of materials, differences in quality and diversity of working methods, we recommend that users perform tests prior to application under actual conditions of use.

This document may be amended in keeping with product development and the state of our knowledge without prior notice and therefore it is recommended to check on <http://www.geb.fr> that you have the latest version before use.