

Technical Data Sheet

E-Labo-044 V11

Issued on: **07/11/2025**

Version: 12

Cancels and replaces previous versions

YARN FILASSE

Functionality

Superior quality combed linen yarn.

- It is used in addition to jointing compounds for sealing metallic threaded joints in contact with hot or cold sanitary water.
- Improves the pressure resistance of fittings, particularly where there is a significant gap.
- For chemicals installations, use GEBETANCHE range.
- For plastic joints, use PATE D'ETANCHEITE MATERIAUX PLASTIQUES.

Technical characteristics

| Characteristics | Specifications | |
|------------------------|---------------------------------|--|
| Quality | Flexible, extra fine, water ret | |
| Temperature resistance | +140 °C | |
| Properties | Good water resistance | |

Use

Preparation

• The fittings must be clean, dry and free of grease.

Instructions for use

- Coat the male fitting with jointing compound.
- Wrap the YARN around male fitting in the same direction of the thread and smooth it.
- Coat again with jointing compound on male fitting over the yarn.
- Assemble and tighten firmly (> 50 N.m).

Safety precautions

The Material Safety Data Sheet is available on the Internet on www.quickfds.com or on www.qeb.fr.

If the product is subject to detergent regulation: Component list available on request at reach@geb.fr

If the product is subject to biocide regulation or if it contains a biocide to protect it: Consult the Material Safety Data Sheet - Please use the products responsiblly.

GEB SAS – CS 62062 – Tremblay en France - 95972 Roissy Charles de Gaulle Cedex – France Tél : 33 (0)1.48.17.99.99 - Fax : 33 (0)1.48.17.98.00 - www.geb.fr

| _ | - | | |
|----|---|---|--------------|
| | | т | \mathbf{a} |
| ı. | | ш | U |

Smooth the piece of yarn between your fingers to remove any knots that may get in the way of the fittings being screwed together.

Storage

Store at a temperature between 0°C and +40°C.

The expiry date on packaging is for unopened product stored at 20°C in normal hygrometry conditions.

Packaging and waste sorting

Refer to the information on the product and to the applicable local regulations.

The information contained on the technical datasheet is provided in all good faith and results from measurements made in our laboratory. Given the number of materials, differences in quality and diversity of working methods, we recommend that users perform tests prior to application under actual conditions of use.

This document may be amended in keeping with product development and the state of our knowledge without prior notice and therefore it is recommended to check on http://www.geb.fr that you have the latest version before use.

GEB SAS – CS 62062 – Tremblay en France - 95972 Roissy Charles de Gaulle Cedex – France Tél : 33 (0)1.48.17.99.99 - Fax : 33 (0)1.48.17.98.00 - www.geb.fr