

FILGUM

Functionality

Butyl rubber based sealant.

- Sealing drain joints.
- Sealing drain pipe joints or mating surfaces.
- Filling.

Technical characteristics

Characteristics	Specifications
Colour	Beige
Appearance	Firm malleable dough
Drying time before use	None The product remains soft and pliable over time.
Temperature resistance	Up to +100°C
Paintability	Yes
Resistance	Good resistance to hot and cold water, alkaline solutions and household cleaning products.
Adhesion	Good adhesion to most materials (metal, aluminium, steel, glass, plexiglass, PVC, wood, concrete, ceramic, a preliminary test is recommended on porous materials such as marble or stone (risk of staining))

Use

Preparation

- The support materials must be free of dust and grease and dry.

Instructions for use

- Take out the required quantity of sealant.
- Knead the putty before application and form a cord.
- Final installation can be done manually or by mechanical clamping.
- Remove and clean any excess of product that may be exceeded after installation.
- Commissioning is immediate.

Consumption

Depending on the diameter covered, a cord of 1 m can be covered with the amount of product :

Cord diameter (mm)	5	10	15	20
Amount of product for 1m of cord (g)	36	145	327	581

Material cleaning

With acetone, white-spirit or ethyl alcohol.

Safety precautions

The Material Safety Data Sheet is available on the Internet on www.quickfds.com or on www.geb.fr .

If the product is subject to detergent regulation : Component list available on request at reach@geb.fr

If the product is subject to biocide regulation or if it contains a biocide to protect it : Consult the Material Safety Data Sheet - Please use the products responsibly.

Tip

To make application easier, knead and form a cord.

Comments

For applications between -5°C and 0°C, make sure there is no condensation on the application surface.

Storage

Store at a temperature between +5°C and +40°C.

The expiry date on packaging is for unopened product stored at 20°C in normal hygrometry conditions.

Packaging and waste sorting

Refer to the information on the product and to the applicable local regulations.

The information contained on the technical datasheet is provided in all good faith and results from measurements made in our laboratory. Given the number of materials, differences in quality and diversity of working methods, we recommend that users perform tests prior to application under actual conditions of use.

This document may be amended in keeping with product development and the state of our knowledge without prior notice and therefore it is recommended to check on <http://www.geb.fr> that you have the latest version before use.