

Technical Data Sheet

E-Labo-044 V11

Issued on: 19/09/2025

Version: 2

Cancels and replaces previous versions

GEBEX PLUS SPRAY

Functionality

100% silicone oil-based lubricant, anti-adhesive and water-repellent

- Lubrication of rubber and plastic materials either individually or in combination.
- Lubrication of all types and all diameters of piping.
- Protection against moisture of distributors, coils, electrical circuits and connectors.
- Anti-adhesive for rubber, prevents seal ageing and deformation.
- Release agent.
- · Prevents adhesion of waxes and binders.
- Ideal in dusty environments.
- Can be used head up or head down.

Technical characteristics

Characteristics	Specifications
Type	100% silicone oil
Temperature resistance	-15°C to +220°C
Water resistance	Excellent

Use

Preparation

• Clean and degrease the surfaces.

Instructions for use

- Shake the can then spray evenly.
- Wait for a while.

Safety precautions

The Material Safety Data Sheet is available on the Internet on www.quickfds.com or on www.geb.fr .

If the product is subject to detergent regulation: Component list available on request at reach@geb.fr

If the product is subject to biocide regulation or if it contains a biocide to protect it : Consult the Material Safety Data Sheet - Please use the products responsiblly.

GEB SAS – CS 62062 – Tremblay en France - 95972 Roissy Charles de Gaulle Cedex – France Tél : 33 (0)1.48.17.99.99 - Fax : 33 (0)1.48.17.98.00 - www.geb.fr

Comments
Comments
Do not use on parts to be subsequently painted or on electric motor brushes
Storage
Storage
Store at a temperature between -5°C and +40°C.
The expiry date on packaging is for unopened product stored at 20°C in normal hygrometry conditions.
Packaging and waste sorting
Refer to the information on the product and to the applicable local regulations.
The information contained on the technical datasheet is provided in all good faith and results from measurements
made in our laboratory. Given the number of materials, differences in quality and diversity of working methods, we
recommend that users perform tests prior to application under actual conditions of use. This document may be amended in keeping with product development and the state of our knowledge without prior
notice and therefore it is recommended to check on http://www.geb.fr that you have the latest version before use.