

PINK CALCIUM GREASE GRAISSE CALCIQUE ROSE

Functionality

Common lubrication of mechanisms operating under moderate conditions.

- Door hinges, trailer hitch, joints, caravan attachments, etc.
- Cardan joints, chassis, roller tracks.
- Protection of tools and flat surfaces against oxidation.

Technical characteristics

Characteristics	Specifications
Colour	Red
Texture	Fairly free-running and adhesive
Penetration	NLGI grade: 2 (265/295)
Drop point	≥ 100 °C
Temperature resistance	-15 °C to +65 °C
Adhesion	Good adhesion to all surfaces
Water resistance	Good water resistance

Use

Preparation

- Clean and degrease all surfaces

Instructions for use

- Apply the grease.

Material cleaning

Solvent-based or water-based cleaner.
White-spirit or acetone.

Safety precautions

The Material Safety Data Sheet is available on the Internet on www.quickfds.com or on www.geb.fr .

If the product is subject to detergent regulation : Component list available on request at reach@geb.fr

If the product is subject to biocide regulation or if it contains a biocide to protect it : Consult the Material Safety Data Sheet - Please use the products responsibly.

Storage

Store at a temperature between +5°C and +40°C.

The expiry date on packaging is for unopened product stored at 20°C in normal hygrometry conditions.

Packaging and waste sorting

Refer to the information on the product and to the applicable local regulations.

The information contained on the technical datasheet is provided in all good faith and results from measurements made in our laboratory. Given the number of materials, differences in quality and diversity of working methods, we recommend that users perform tests prior to application under actual conditions of use.

This document may be amended in keeping with product development and the state of our knowledge without prior notice and therefore it is recommended to check on <http://www.geb.fr> that you have the latest version before use.