

Technical Data Sheet

E-Labo-044 V11

Issued on: 19/09/2025

Version: 10

Cancels and replaces previous versions

PARAFFINE PARAFFINE

Functionality

Refined food grade paraffin wax for industrial, decorative, food and cosmetic use. For use in solid or liquid form after melting.

- Solid lubrication particularly for wood.
- Screwing agent in hard wood.
- Damp proofing of porous surfaces.
- Candles.
- Protection of preserves.

Labels and Accreditation

Authorised for contact with foodstuffs:

- Brochure 1227
- FDA CFR21

Technical characteristics

Characteristics	Specifications
Appearance	Solid
Colour	White
Odour	Odourless
Density	0.9
Melting point	Between 58°C and 60°C
Viscosity at 100°C	3 cst
Good insulating properties	

Use

Lubrication:

Preparation

As required, degrease beforehand.

GEB SAS – CS 62062 – Tremblay en France - 95972 Roissy Charles de Gaulle Cedex – France Tél : 33 (0)1.48.17.99.99 - Fax : 33 (0)1.48.17.98.00 - www.geb.fr

Instructions for use

· Rub the surfaces in contact with the stick.

Waterproofing:

Preparation

As required, melt the stick at a temperature greater than 57°C.

Instructions for use

• Depending on the materials, apply the PARAFFIN solid or melted

Material cleaning

With solvent or heat at over 60°C.

Safety precautions

The Material Safety Data Sheet is available on the Internet on www.quickfds.com or on www.geb.fr.

If the product is subject to detergent regulation: Component list available on request at reach@geb.fr

If the product is subject to biocide regulation or if it contains a biocide to protect it: Consult the Material Safety Data Sheet - Please use the products responsiblly.

Storage

Store at a temperature between +5°C and +40°C.

The expiry date on packaging is for unopened product stored at 20°C in normal hygrometry conditions.

Packaging and waste sorting

Refer to the information on the product and to the applicable local regulations.

The information contained on the technical datasheet is provided in all good faith and results from measurements made in our laboratory. Given the number of materials, differences in quality and diversity of working methods, we recommend that users perform tests prior to application under actual conditions of use.

This document may be amended in keeping with product development and the state of our knowledge without prior notice and therefore it is recommended to check on http://www.geb.fr that you have the latest version before use.