

Technical Data Sheet

F-Labo-044 V11

Issued on: 01/08/2025

Version: 8

Cancels and replaces previous versions

ROULEAU D'ATELIER WORKSHOP ROLLER

Functionality

Abrasive cloth for all deburring, sanding, rust removal, polishing and chamfering work on metals and plastics, even in damp conditions.

- Plumbers, heating engineers, installers: preparation of pipes and joints (copper, steel, PVC, etc.) before welding or gluing.
- Automotive industry: deburring, cleaning of sheet metal, etc.
- Mechanical engineering: deoxidisation of metals, deburring, maintenance, etc.
- Very flexible cloth that can be easily torn by hand, allowing you to work on small diameters and reach the most inaccessible burrs.
- Very practical dispenser that makes cutting easy and protects against dust.

Technical characteristics

Characteristics	Specifications
4 grain sizes available	60 - 80 - 100 - 120
Material	Cotton cloth
Grain type	Brown Corydon
1st collage in contact with media	Phenolic resin
2 nd collage	Phenolic resin
Use in wetlands	Yes
Tearable by hand	Very easy

Use

Instructions for use

- Tear off a piece of the strip by hand.
- Carry out the work as required.

Safety precautions

The Material Safety Data Sheet is available on the Internet on www.guickfds.com or on www.geb.fr.

If the product is subject to detergent regulation : Component list available on request at reach@geb.fr

If the product is subject to biocide regulation or if it contains a biocide to protect it: Consult the Material Safety Data Sheet - Please use the products responsiblly.

GEB SAS – CS 62062 – Tremblay en France - 95972 Roissy Charles de Gaulle Cedex – France Tél : 33 (0)1.48.17.99.99 - Fax : 33 (0)1.48.17.98.00 - www.geb.fr

T_GB_ROULEAU_D_ATELIER- page 1 sur 2

Storage Storage
Store at a temperature between 0°C and +40°C. The expiry date on packaging is for unopened product stored at 20°C in normal hygrometry conditions.
Packaging and waste sorting
Refer to the information on the product and to the applicable local regulations.
The information contained on the technical datasheet is provided in all good faith and results from measurements made in our laboratory. Given the number of materials, differences in quality and diversity of working methods, we recommend that users perform tests prior to application under actual conditions of use. This document may be amended in keeping with product development and the state of our knowledge without prior notice and therefore it is recommended to check on http://www.geb.fr that you have the latest version before use.
GEB SAS - CS 62062 - Tremblay en France - 95972 Roissy Charles de Gaulle Cedex - France
Tél : 33 (0)1.48.17.99.99 - Fax : 33 (0)1.48.17.98.00 - www.geb.fr